



Blindnietmutter FO-S5



Materialausführungen


Blindnietmutter (FO-S5)

Flachkopf offen, Stahl Sechskantschaft

Oberfläche: verzinkt

Die Oberfläche ist RoHS konform

Sonderabmessungen auf Anfrage



Gewinde M	d	h	Blechdicke (g)	s	Ø b	a
M4	5,9	11,5 13,0	0,5 - 2,0 2,5 - 5,0	6,0	9,0	1,0
M5	6,9	13,5 15,0	0,5 - 3,0 3,0 - 6,0	7,0	10,0	1,0
M6	8,9	15,5 18,0	0,5 - 3,0 3,5 - 6,0	9,0	13,0	1,5
M8	10,9	17,5 20,0	0,5 - 3,0 4,0 - 6,0	11,0	16,0	1,5
M10	12,9	22,0 24,0	1,0 - 4,0 4,0 - 6,5	13,0	17,0	1,8
M12	15,9	25,0	1,0 - 4,0	16,0	23,0	2,0

Maße in mm

Bitte senden Sie
Ihre Anfrage an:

Email: vertrieb@ael-gmbh.de
Telefon: +49 2354 9046 24
Adresse: Auf dem Bamberg 4
58540 Meinerzhagen



Management
System
ISO 9001:2015